

dalla corte dc pro



dc pro / 3 groups / high version

A dc pro high group version is available from now on: it is suitable for places that serve coffee in large size mugs and take-away glasses, and it is characterized by the presence of the element covering the group on the top grate, with a 16 cm maximum distance between the surface on which cups rest and the groups themselves; another small grate permits to have the cup closer to the spout when extracting an espresso. This new version meets the requirements of the Australian market, of some areas in the United States and cafeterias in Northern Europe.



dimensions (w x h x d)	(mm)	940x540x510
weight	(kg)	88
power consumption (24h-stand-by)	(kw)	11,3
max power	(kw)	5,1
connected load		230 V 1 Ph, 200/230 V 3, 400 V 3N - 50/60 Hz
boiler capacity	(l)	13
capacity of group heads	(l)	0,5
serial connection		RS 232/485
low power system (LPS)		included
timer		included
rear-lightning		included

options

MCS (milk-control-system)	you need an additional steam wand
GCS (grinder-control-system)	you need a dc II or a dc one grinder
OCS (online-control-system)	you need a pc and a connection cable
multigrinder kit	for the connection of 2 or 3 dc one grinders



3 groups classic aluminium/white



part number:
1-MC-DC-PRO-3-B-400

3 groups classic aluminium/black



part number:
1-MC-DC-PRO-3-N-400

3 groups industrial titanium/stainless steel



part number:
1-MC-DC-PRO-3-T-400

3 groups dynamic white/stainless steel



part number:
1-MC-DC-PRO-3-W-400